## In The Claims:

1. (Currently Amended) A memory module for operation in a data memory system, comprising:

a plurality of data memory devices for storing useful data, wherein the data memory devices are configured as DRAM modules;

at least one buffer device connected to the data memory devices <u>by</u> at least <del>via</del> data lines, and serving to condition at least data signals, the data signals being transferred on the data lines between the data memory devices and a memory <u>control</u> ehecking device of the data memory system; and

at least one buffer and error checking module, which in each case integrates a buffer device and a data memory device for storing redundancy data operable to detect and to correct erroneous data in a common device housing.

- 2. (Currently Amended) The memory module of claim 1, wherein each of the buffer and error checking modules is connected to an even number of data memory devices for storing the useful data.
- 3. (Original) The memory module of claim 2, wherein the data memory devices are arranged symmetrically with respect to the buffer and error checking module.
- 4. (Currently Amended) The memory module of claim 1, wherein the buffer and error checking module has an error detecting unit operable to perform the following: [[,]]

during a transfer of useful data to the memory module, to form and to store the redundancy data; and [[,]]

during a transfer of useful data to the memory control ehecking device, to form check data from the useful data to be transferred and also to compare respectively corresponding redundancy data and with the check data.

- 5. (Currently Amended) The memory module of claim 4, wherein the buffer and error checking module has an error correction unit operable to correct erroneous useful data on the basis of respectively corresponding redundancy data and check data.
- 6. (Currently Amended) The memory module of claim 5, wherein the memory module is absent a contact device assigned to a data line for transferring redundancy data any error correction is performed exclusively on the memory module and without communication with the memory control device.
- 7. (Currently Amended) The memory module of claim 5, wherein the memory module has an error signaling unit operable to transfer information on error events to the memory <u>control</u> ehecking device.
- 8. (Original) The memory module of claim 5, wherein the buffer and error checking module has an error evaluation unit operable to identify and to mask out defective memory cells in the data memory devices.

- 9. (Canceled)
- 10. (Original) The memory module of claim 1, wherein the data memory devices comprise a DDR interface.
- 11. (Original) The memory module of claim 1, wherein the maximum dimensions of the memory module are about 1.2 inches x 5.25 inches.
- 12. (Currently Amended) A buffer and error checking module for memory modules, the memory modules comprising in each case a plurality of DRAM devices operated in data memory systems, the buffer and error checking module comprising:

connecting devices;

a buffer/redriver formed in a semiconductor substrate and operable to condition at least data signals that are transferred to and from the memory modules; and

a memory cell array formed in the semiconductor substrate as an error data memory.

13. (Currently Amended) The buffer and error checking module of claim 12, further comprising an error detecting unit operable, during a transfer of useful data to the memory module, to form and to store redundancy data and, during a transfer of useful data to a memory control ehecking device of the data memory system, to compare the stored redundancy data with check data formed from the useful data to be transferred.

- 14. (Currently Amended) The buffer and error checking module of claim 13, further comprising an error correction unit operable to correct erroneous useful data on the basis of respectively corresponding redundancy data and check data.
- 15. (Original) The buffer and error checking module of claims 13, further comprising an error signaling unit operable to transfer information on error events to the data memory system.
- 16. (Original) The buffer and error checking module of claim 13, further comprising an error evaluation unit operable to identify and to mask out defective memory cells in data memory devices connected to the buffer and error checking module.
- 17. (Currently Amended) A method for operating a memory module having a plurality of data memory DRAM devices for storing useful data and at least one buffer and error checking module in a data memory system, the method comprising:

receiving data signals of useful data transferred to the memory module and conditioning the data signals with the buffer and error checking module;

forming, in the buffer and error checking module, a corresponding set of redundancy data with respect to the useful data;

storing the useful data in the data memory DRAM devices;

storing the respectively corresponding set of redundancy data in the buffer and error checking module;

forming in the buffer and error checking module, during a transfer of stored useful data from the data memory DRAM devices to a memory control checking device of the data memory system, a corresponding set of check data;

detecting, through a comparison of respectively corresponding redundancy data and check data, data errors that have occurred in the useful data are and correcting any such errors on a case by case basis; and

transferring corrected and essentially error-free useful data to the memory control checking device.

- 18. (Currently Amended) The method of claim 17, further comprising signaling an occurrence of a data error in the useful data to the memory control ehecking device of the data memory system.
- 19. (Currently Amended) The method of claim 17, further comprising optimizing a data memory system by:

providing a redundancy bus system in precursor systems on a system board between a memory control ehecking device and the memory module;

registering transfer errors in the bus system and analyzing, in the precursor systems, the transfer errors by the memory <u>control</u> <u>ehecking</u> device with the aid of the redundancy bus system;

developing, on the basis of an analysis of transfer errors occurring between the memory control checking device and the memory module, a bus system of respective precursor systems in a direction of a minimum number of transfer errors; and

providing the data memory system with the bus system developed for a minimum number of transfer errors.

20. (Canceled)